



CROIX DE FER 40

Colour: **Sterling Gloss**

SPECS

Frame	Reynolds 725, 142mm OLD, 12mm TA
Fork	Genesis CrMo, 1-1/8" Steerer, 100mm OLD, 12mm TA
Headset	EC34/EC34

BRAKES

Brakes	Shimano GRX BR-RX610, 160mm/160mm, Hydraulic
--------	--

DRIVE TRAIN

Shifters	Shimano GRX ST-RX610 1x12sp
Front Derailleur	N/A
Rear Derailleur	Shimano GRX RD-RX822 12sp
Chainset	Shimano GRX FC-RX610-1, 40T, 170mm (XS-SM-MD), 175mm (LG-XL)
BB	Shimano BSA 68mm
Chain	KMC X12
Cassette	Shimano M710 10-45T

WHEELS & TYRES

Rims	Amplitude G-100, 622x26, 32h
Hubs	KT T20 - RR615, 32H, CL
Spokes	Double Butted 14G Stainless
Tyres	Maxxis Rambler 700x45c TR

COMPONENTS

Handlebars	Amplitude G-100, 420mm (XS), 440mm (SM-MD), 460mm (LG-XL)
Grips/ Tape	Black Gel Tape
Stem	Amplitude G-100, 70mm (XS), 80mm (SM), 100mm (MD, LG, XL)
Seat Collar	Alloy, 29.8mm
Seatpost	Amplitude G-100, 27.2mm x 350mm
Saddle	Madison Flux Switch 142mm x 280mm
Pedals	N/A

HIGHLIGHTS

- Shimano GRX 1x12sp drivetrain.
- Increased tyre clearance, now specified with 700x45c tyres. Maximum clearance 45mm with mudguards or 47mm without mudguards.
- Shimano GRX hydraulic braking.
- Dropper post compatible.
- Tubeless compatible rims, tyres and rim tape with tubeless valves also supplied.

GEOMETRY	XS	S	M	L	XL
Seat Tube	470	490	530	560	590
Top Tube	553.2	557.2	558.2	573.8	589.4
Frame Stack	551.6	565.8	584.7	603.6	622.5
Frame Reach	395	395	385	395	405
Head Tube	100	115	135	155	175
Head Angle	71	71	71	71	71
Seat Angle	74	74	73.5	73.5	73.5
BB Drop	73	73	73	73	73
Fork Offset	50	50	50	50	50
Wheelbase	1041.5	1046.4	1042.9	1059.4	1075.9
Handlebar Width	420	440	440	460	460
Stem Length	70	80	100	100	100
Reach + Stem	465	475	485	495	505